

Winpower CPB-2000LAU

Mobile Phone with UHF Immobilize System

CPB-2000LAU Cellular Phone with UHF BREAKER

A. Specification

| | |
|----|--|
| 01 | TX frequency 850 ~ 2170 MHz |
| 05 | TX frequency 100 ~ 500 MHz |
| 06 | Total output power include 3G : 60W |
| 07 | Cover interface standards: AMPS,N-AMPS, NMT, TACS, GSM, CDMA, TDMA, iDEN, UMTS. FRS, UHF |
| 08 | All the TX frequency covered down link only. |
| 09 | RF output indicating of LED display |
| 10 | Switch ON/OFF outer. |
| 11 | Three fans of convection with filter. |
| 12 | 5 Panel Antennas integrated of cellular phone band. |
| 13 | External N type antenna connecter. |
| 14 | Jamming distance : 50 meters. |
| 15 | The outer power input from AC 100 ~ 240V |
| 16 | Built in lithium battery (re-chargeable) can support 2hours operating time. |
| 17 | Indicating of LED display, included Charging · Battery full · Battery low |
| 18 | Operating temperature : -10°C ~ +60°C |
| 19 | Can support use while battery charging |
| 20 | Dimension : 56(L) × 45.5(W) × 26.5(H)cm |
| 21 | Weight : 26 Kg (Not include external antennas) |
| 22 | Operating temperature : -10°C ~ +60°C |
| 23 | Humidity : 5% ~ 80% |
| 24 | Device housed in a trolley-style, ruggedized pelican case |

