

Winpower WP-VS200GT

MPEG-4 Real-Time Networking Camera

Winpower's WP-VS200GT Features

- MPEG-4 Compression Engine
- Motorized Pan/Tilt
- DDNS Support
- Intelligent Motion Detection
- Alarm Snapshots
- .Extended I/O for sensor & Alarm
- Free-Bundled Recording Software



Key Specifications / Special Features

Camera Specifications

1/3 inch color CCD image sensor.
512(H) x 492(V)(NTSC)
512(H) x 582(V)(PAL)
0.2Lux / F 2.0
AGC, AWB, AES

Lens

Board Lens 8.0mm F2.0, Option: 12.0mm

Networking

Protocol: TCP/IP, SMTP, FTP, DHCP, NTP, ICMP, PPPoE, DDNS, ARP, RTP/RTCP, RTSP and ICMP.

Ethernet: 10 base T or 100 base T fast Ethernet auto negotiation.

System SD card for video storage. Firmware upgrade by Ethernet, Watchdog.

Pan/Tilt Pan: range 0°~325°, Tilt range 10°~90°, Auto patrol mode, Ethernet control interface.

Microphone Omni-directional, Frequency 20~20000Hz, S/N ratio more than 55dB.

Video MPEG4 Codec.

Features: Adjustable image size and quality.
Time stamp and text overlay.
Intelligent motion detection.
Video output connector.
Resolution Up to 30frames at 1024x768

Security

2 levels for administrator and user group.
Password authentication.

Viewing System Requirement

Operation system: Microsoft Window 98, ME, 2000, XP.
Browser Internet Explorer 5.0 or above.

General I/O Trigger

2 alarm input, 12VDC 50mA, 1 Nc/No relay output, Contact rating [3A@125VAC/30VDC](#)

LED Indicators

System power and status indicators, system activity and Network link indicators.

Operating Environment Temperature: -10°C~50°C (14~122F), Humidity: 10%~80%.

Dimension Length:133mm, Width 146mm, Height 164mm

Weight 800g

EMI & Safety CE, FCC